



## PETROMAX ATF TYPE A

### PRODUCT DESCRIPTION:

PETROMAX ATF Type A is a high-quality automatic transmission fluid designed for vehicles requiring General Motors Type A Suffix A fluids. Formulated with highly refined base oils and advanced performance additives, this fluid offers superior thermal stability, optimal frictional properties, and robust rust and corrosion protection. It not only meets but surpasses the performance standards of the General Motors Type A Suffix A specification, making it an excellent choice for automatic transmissions and power steering systems.

### APPLICATION:

Recommended for automatic transmissions and power steering systems in vehicles that require General Motors Type A Suffix A quality fluids. It is also suitable for certain manual transmissions and hydraulic systems where this type of fluid is specified.

### FEATURES & BENEFITS:

- Excellent oxidation and thermal stability minimise deposit formation.
- Offers superior anti-wear protection for critical components.
- Extremely high viscosity index ensures reliable lubrication across a wide range of temperatures, from low starting to high operating conditions.
- Provides robust protection against rust and corrosion.
- Enhanced low-temperature fluidity ensures efficient cold-start performance.
- Effective foam control promotes smooth gear shifting.
- Compatible with all standard seal materials.

### PERFORMANCE LEVEL MEETS:

GM Type A Suffix A

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	PETROMAX TYPE A
Kinematic Viscosity @ 104° F / 40° C	ASTM D7042	cSt	38.25
Kinematic Viscosity @ 212° F / 100° C	ASTM D7042	cSt	7.2
Viscosity Index	ASTM D2270	-	155
Density @15° C/ 60° F	ASTM D4052	g/cm <sup>3</sup>	0.86
Flash Point (max)	ASTM D92	°C	210
Pour Point (max)	ASTM D97	°C	-35

Note: The characteristics mentioned above are typical values and should not be considered product specifications.

### Health and Safety

PETROMAX oil, when used as directed and with proper personal hygiene, is not expected to pose significant health or safety risks. It's important to avoid skin contact and utilise gloves when handling used oil. In case of skin exposure, promptly wash with soap and water. For detailed Health and Safety guidelines, refer to the corresponding Safety Data Sheet accessible at <https://petromaxindustries.com>.

### Protect the Environment

Please ensure to dispose of used oil at a facility authorized for collection. Do not release it into drains, soil, or water sources.

### Storage

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possibility of water ingress and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.